

RIGMASTER™ LED SERIES LUMINAIRES

STANDARD OR WITH EMERGENCY BATTERY BACKUP — HAZARDOUS LOCATIONS

FEATURES

- Lightweight and low profile luminaire, perfect for low clearance, obstructed areas or compact spaces
- Available in two sizes and output options, delivering up to 7600 lumens
- Adjustable yoke brackets (0°, 15°, 30°, 45°, 60° and 90°) with fixture position locking mechanism and various bolt patterns that accommodate most bolt patterns from Crouse-Hinds™ †, Dialight™ ‡ and other manufacturers
- Optional field installable pendant mount kit provides top wire entry applications
- Select a clear or diffused polycarbonate lens for the optimal level of work plane brightness and visual comfort. These lenses are field interchangeable for convenience and flexibility
- 5 casted points standard for secondary safety retention.
- 90 or 180 minutes of emergency battery backup optional
- Loop in/out wiring capability for interconnecting fixtures
- Hinged wire compartment cover is secured with captive screws for safety and convenience

WARRANTY

- 5 year warranty on standard fixture. 3 year warranty on emergency fixtures

TYPICAL APPLICATIONS

- Pulp and paper mills
- Drilling rigs
- Oil refineries

- Grain loading areas
- Petrochemical facilities
- Waste and sewer treatment
- Underground tunnels
- Analyzer houses
- Cooling towers
- Grain elevators
- Coal and metal manufacturing
- Flour and feed mills
- Hydrogen and Biofuels plants
- LNG (Liquid Natural Gas) plants

LUMINAIRE MATERIALS

- Housing: copperfree (4/10 of 1% max.) aluminum
- Lens: thermal shock- and impact-resistant polycarbonate
- Gasket: silicone rubber
- Bolts: stainless steel
- Close up plugs: (3) aluminum provided
- Mounting brackets: zinc plated steel

ACCESSORIES (PURCHASE SEPARATELY)

- Pendant Mount Kit: RMPENDKIT / RMHPENDKIT
- Beam clamp kit: RMBCKIT
- Safety Cable: LEDSC

NEC/CEC LISTINGS

- NEC: Class I, Division 2, Groups A, B, C, D | Class II, Division 1, Groups E, F, G | Class II, Division 2, Groups F, G | Class III
- CEC: Class I, Zone 2, Group IIC | Class II, Zone 20 and 21, Group IIIC
- Type 3R, 4, 4X
- IP66



RM*2 + Clear Lens (No Mount)



RM*4 + Clear Lens (No Mount)

- IK10
- 10G vibration on small/large brackets; 5G vibration on low profile bracket and emergency luminaires
- Simultaneous Exposure
- Suitable for Use in Wet Locations
- Marine Outside Type (Salt Water)

NOTABLE LISTINGS

- ABS Certified
- Dark Sky (IDA) Approved
- DLC listed

RELATED PRODUCTS

- Explosionproof Rigmaster LED Series Luminaires
- Industrial Rigmaster LED Series Luminaires

† Crouse-Hinds is a registered trademark of Eaton Corporation.
‡ Dialight is a registered trademark of Dialight.

PRODUCT SPECIFICATIONS

Series * Lumen Output	RM*2	RM*4
Nominal Wattage (W, @120 V)	33	55
Equivalencies (W, T8)	2 x 32W	3 x 32W
Nominal Lumens Standard Mode ❶	4390	7650
Nominal Lumens Emergency Mode ❶	1350 (90 min) 800 (180 min)	
Efficacy (up to, lm/W)	133	139
Color Temperature (CCT) (K)	5000/4000/3000	
Color Rendering Index (CRI)	≥ 80 CRI	
Voltage	120-277 Vac, 50/60 Hz; 125-300 Vdc 347-480 Vac, 50/60 Hz	
Surge Protection	6 kV, 3 kA	
L70 Lifetime (hrs, reported)	60,000 hours @ 40 °C	
Ambient Temperature ❷	Standard: -40 °C to +65 °C (-40 °F to +149 °F) Emergency: -20 °C to +55 °C (-4 °F to +131 °F)	
Temperature Code ❷	T4 - T6	
Fixture Weight Standard Model - kg (lbs)	3.7 (8.2)	4.6 kg (10.1)
Fixture Weight Emergency Model - kg (lbs)	7.6 (16.8)	8.6 kg (19.0)
Replaceable Parts	Driver, Lens, Battery Management Module, Battery Pack	

❶ Nominal lumens based 5000K CCT with clear polycarbonate lens. Refer to catalog pages for detailed performance.

❷ Refer to catalog pages for detailed temperature tables/operating temperature based on lumen output/certification.

APPLETON™

For product information:
www.masteringled.com
1.800.621.1506


EMERSON™

CONSIDER IT SOLVED™

RIGMASTER™ LED SERIES LUMINAIRES

STANDARD OR WITH EMERGENCY BATTERY BACKUP — HAZARDOUS LOCATIONS

Project Information	Specifications
Part Number: _____ Date: _____	_____
Project: _____	_____
Fixture Type: _____	_____

CATALOG NUMBERING GUIDE

Series Prefix	Lumen (nominal)	Color Temperature	Light Distribution Pattern	Emergency	Wiring Method	Option
RM			L		G	

SERIES PREFIX: RM Rigmaster LED MOUNTING: ④ A Small Swivel Bracket ⑤ B Large Swivel Bracket L Low Profile Bracket N If None (Use if Ordering Appleton Bracket Separately) LUMEN (NOMINAL): ② 2 4,300 Lumens (2') 4 7,600 Lumens (4')	HUB SIZE: 1 (4) 1/2" NPT 2 (4) 3/4" NPT COLOR TEMPERATURE (CCT): C Cool, 5000K N Neutral, 4000K W Warm, 3000K LENS MATERIAL: D Diffused Polycarbonate P Clear Polycarbonate	LIGHT DISTRIBUTION PATTERN: L Linear Pattern VOLTAGE: BU 120-277 Vac, 50/60 Hz; 125-300 Vdc BH 347-480 Vac, 50/60 Hz ① EMERGENCY: ⑥ N If None (Standard) H 90 Minutes E 180 Minutes	COLOR: G Appleton Gray (Standard) WIRING METHOD: W Wire Nuts (Standard) T Fixed Terminal Block ③ OPTION: ④ Blank If None 1 (1) Safety Cable 2 (2) Safety Cables
---	--	---	--

- ① Marine Outside Type (Salt Water) is applicable to standard (non emergency) fixtures only.
- ② Refer to catalog pages for detailed lumen output information, see Lumen Output (Efficacy) Table.
- ③ Terminal block option available for standard unit, BU voltage configuration only.
- ④ Brackets and safety cables can be ordered separately or included with fixture. Refer to catalog pages for more information.
- ⑤ Mounting option A is not available with emergency version.
- ⑥ Emergency battery back up version is only available with BU voltage configuration for 120-277 Vac operation.

DIMENSIONAL DRAWINGS • | MILLIMETERS (INCHES)

RM*2 Standard Model 	RM*4 Standard Model 	RM*2 and RM*4 End View
With Emergency Battery Backup 	With Emergency Battery Backup 	End View

• Models shown with no mounting bracket. Refer to catalog pages or the Product Drawing configurator page for additional dimensional information; available on www.masteringled.com.